

# STAUF

— seit 1828 —




## STAUF ACTIVATOR

Solvent-free activator for STAUF 2C-PU products for activating the hardening process in indoor and outdoor use


### Technical Datasheet

Product number	✓ 125213
Special features	✓ solvent-free ✓ reduces waiting times ✓ easy to use ✓ easy dosage
Color	✓ colorless
Required quantities per m <sup>2</sup>	✓ depends on desired processing time at low ambient air temperatures, Activator admixture STAUF R 201 max. 6g (0.05%) / bucket, ✓ Activator admixture STAUF R 105 max. 4g (0.05%) / bucket, ✓ Activator admixture STAUF PUK 445/ 446 max. 45g (0.5%) / bucket, ✓ Activator admixture STAUF PU filler max. 73g (0.5%) / bucket
Shelf-life	✓ 6 months
Available packaging	✓ 200 g plastic can



### PROCESSING

Use the enclosed plastic pipette to add the activator when the hardener is added to the mix and stir until a homogenous compound is achieved. A half-filled pipette corresponds to approx. 5 gr of the catalyst solution. Tests on site are required since conditions can vary significantly. Do not exceed the maximal recommended amount. The product pot life and open time in particular is reduced after adding and mixing the activator.



## LIMITATION OF LIABILITY

The foregoing representations are based on the results of our most current product and material testing and are of a non-obligatory advisory nature only since we have no control over the actual quality of workmanship, materials used and worksite conditions. As such, they do not constitute an express or implied warranty of any kind. The same applies to our commercial and technical consultation services which are provided free-of-charge and without obligation. Therefore, we strongly recommend that prior on-site testing be conducted to observe and study the suitability of the product for the intended purpose. With the release of this technical information, all prior technical information (technical data sheets, installation recommendations and other information regarding similar purposes) becomes invalid.

**STAUF KLEBSTOFFWERK GMBH** . Oberhausener Str. 1 . 57234 Wilnsdorf . Germany  
Fon: +49 (0) 2739 301-0 . Fax: +49 (0) 2739 301-200 . Email: [info@stauf.de](mailto:info@stauf.de)

26.01.2018 - 12:04:13